



Cell: 770.630.9258
 Fax: 770.978.2059

2850 Main St. West
 Snellville, GA 30078

www.coatingsinternationalLLC.com

Theoretical Coverage

Square feet/Gallon = $\frac{1600 \times \% \text{ efficiency}}{\text{Thickness in MILS}}$

Applied Thickness Inches	Applied Thickness Mils	Theoretical Coverage sq.ft./Gal @100% Efficiency	Applied Weight lb/sq.ft.	Cost per sq.ft. @ \$30/Gal.	Cost per sq.ft. @ \$35/Gal	Cost per sq.ft. @ \$40/Gal
1/32	31.25	51.20	0.179	\$.59	\$.68	\$.78
1/16	62.50	25.60	0.357	\$1.17	\$1.37	\$1.56
1/8	125.00	12.80	0.715	\$2.34	\$2.73	\$3.13
5/32	156.25	10.24	0.894	\$2.92	\$3.42	\$3.91
3/16	187.50	8.53	1.073	\$3.51	\$4.10	\$4.69
1/4	250.00	6.40	1.430	\$4.68	\$5.47	\$6.25

Coating Coverage

Square feet of Coating, 1 mil Thick

Percent Efficiency of Application	60	65	70	75	80	85	90	95	100
100% solids Percent by Volume	960	104	1120	1200	1280	1360	1440	1520	1600